caroma

Caravelle 600

Vitreous China Under Counter Vanity Basin

Nominal Size 600mm x 425mm

CI/SfB |(74.2) | g3 | Date July 2008

Supersedes all previous issues

2.05.2



Caravelle 600

Vitreous China Under Counter Vanity Basin

Basin Size: 600mm x 425mm (nominal)



A classically styled elliptical under counter vanity basin featuring a large spacious bowl area for quality vanity applications. The deep bowl incorporates smooth contours for ease of cleaning. The rim is sealed to the underside of the counter top with an acetic cured silicone sealant.

Tap Holes: Basin available as no taphole Code No. 659405.

Waste Outlet: The basin has been designed for the Caroma Uni-waste outlet suitable for a

40mm trap connection.

Coloured plastic flush fitting Uni plug and waste supplied. For applications where a chrome plated brass waste is required there are four suitable Uniwastes available in the following options — Flush Fitting Plug and Waste Code No.687140, Vandal Resistant Flush Fitting Plug and Waste Code No.687141, Covered Plug and Waste Code No.687142 and Vandal Resistant Covered Plug

and Waste Code No.687143.

Installation: The Caravelle 600 is suitable for installation under Polyester, Marble, Natural

Stone or other suitable impervious materials.

Bowl Capacity: 12.5 litres to overflow.

Overflow: Overflow available only. Designed for maximum tap flow rate of 15 litres/minute.

Fixing: Aluminium Clip Bracket Code No.813734 supplied as standard for fixing basin to marble or granite counter tops. Alloy Bracket Code No.811326 (not supplied) is available as an option for fixing basin to wooden counter tops. Four brackets are supplied with each basin and must be fixed to the underside of the counter top

with appropriate fasteners.

The rim of the basins must be sealed to the counter top with an acetic cured

silicone sealant. Epoxy type glues must not be used.

The basin is supplied with a template which must be used for the counter top

cut-out.

Colours: White only.

Dimensions: All dimensions are in millimetres and are subject to normal manufacturing

variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications

without notice.

