## **KREOS** BASIN

### NATURAL STONE



#### Above counter basin, rectangular.

- Solid natural stone, smooth honed finish.
- Matching stone waste included.

ORDER CODE 191097 Smoke

191098 Sand

191099 Midnight

TAPHOLE No taphole.

WASTE Supplied, stone cap.

OVERFLOW No overflow.


MATERIAL

COLOUR Three colour options, see below.

Natural stone.

FIXING Always use the actual basin to verify cutout.

Use silicone sealant. Do not use epoxy type adhesives.





NATURAL STONE **SMOKE** 





NATURAL STONE **SAND** 

NATURAL STONE **MIDNIGHT** 



### Please note

- All measurements are in millimetres.
- Dimensions are nominal and subject to normal manufacturing variations of ±5mm.
- Fixing: Use silicone sealant. DO NOT USE EPOXY TYPE ADHESIVES.
- Always use the actual basin to verify cutout.
- ${\mathord{\hspace{1pt}\text{--}\hspace{1pt}}}$  Specifications may vary without notice as part of our continuous improvement practices.
- Clean with a damp cloth. Do not use abrasive cleaners, liquids or pastes.

# Natural stone basins

## Care and maintenance guide

## Tips for looking after your natural stone basin

The honed surface of your natural stone basin is already sealed when you receive it. This means your basin has been treated with a water-repellent sealant that has penetrated the surface of the stone to help repel liquids.

Your natural stone basin needs care to preserve its beauty. Here are some basic guidelines:

- For daily maintenance, clean the natural stone surface with a soft cloth and warm soapy water or use a professional non-abrasive PH-neutral stone cleaner.
   Rinse, then dry with a soft cloth.
- Seal the surface of your basin at least every 2 years using a water-based sealer for natural stone.
- We recommend that you use professional stone sealing products such as Lithofin MN Stain-Stop.

### Sealing the surface

The basin has already been sealed after manufacture. We recommend that you protect the surface by sealing it with professional stone sealer at least every 2 years. Follow the manufacturer's instructions carefully.

The instructions below are a guide:

- Clean the basin with a soft cloth and warm water. Do not to use acid or alkali cleaners as these may damage the surface.
- Use a hair dryer to dry the surface.
- Using a clean soft cloth, wipe sealant onto the surface of the basin evenly.
- Wait for 10-20 minutes to let the surface dry naturally, then wipe over the surface again. Repeat this process for 2-3 times.
- When the basin is dry, it can be used.

### Caring for natural stone

Natural stone is porous and needs to be sealed so that the surface repels water and other liquids.

- Unsealed stone is susceptible to staining and may absorb moisture.
- Wipe up any spills immediately.
- Do not allow surface deposits to build up on the stone surface, eg soap, salts.
- Thoroughly rinse and dry the stone surface after washing.
- Do not use acid or alkilis on natural stone, including: acidic cleaners, ammonia, abrasive cleaners, vinegar, alcohol, window cleaner, lemon.
- Do not rub the stone surface with abrasive materials or substances. Stone can be scratched by grit and abrasive items. Do not use abrasive pads or cleaning agents, steel wool, metal brushes etc.
- It is possible to hand polish the stone surface using a stone polishing pad. Our natural stone basins come with a semimatte honed finish, rather than a glossy high polished finish.

