

A 90cm stainless steel canopy rangehood with slide controls RRP  ${\rm AUS}~\$379.00$ 





# **Product Details**

#### **FEATURES**

Stainless steel finish Slide controls 3 fan speed options Auto thermal cutout safety

switch

Optional carbon filter(s) Recirculating option (Kit Optional Extra Length Flue

AR500RK) Cover (AR500FS)

#### **BENEFITS**

Removes odours and steam while cooking

Chef rangehoods are designed to remove unwanted odours and greasy steam during cooking, keeping the kitchen fresher and cleaner.

Flexible Installation options

Chef provides additional flexibility when installing your rangehood with the option to recirculate or duct

Keeping the air clean

Carbon filters given the extra odour filtration required when ducted installation is not an option for your kitchen

Easy to maintain

Filters are easy to remove and can be washed in the dishwasher



# **Specifications**

## PRODUCT PROFILE

Domestic warranty details (yrs)	2
Type of Rangehood	wall mounted canopy
Design family (eline)	Chef
Nominal width	90
Finish of Rangehood	stainless steel
	·

#### MOTOR/FAN

Number of fans	2
Number of fans speeds	3
Variable speed control	No
Type of motor	centrifugal
Maximum airflow M3/Hr	550
Noise level dB high	55
Noise level dB low	48

## **DIMENSIONS**

Total product height (mm)	230
Total product width (mm)	900
Total product depth (mm)	500
Diameter of ducting (mm)	125
Minimum installation height from cooking surface Gas (mm)	650

## POWER

Connection plug 10
1 0



#### **DIMENSIONS**

Minimum installation height from cooking surface Electric (mm)

Maximum canopy chimney height (mm)

Flue cover depth (mm)

1240

Flue cover width (mm)

222

## **CONTROLS**

Control panel	switch and slide
Safety/ display indicators	auto thermal cutout safety switch

## **FILTERS**

Number of filters	2
Type of filter	multi layer stainless steel
Dishwasher safe	Yes

#### **LIGHTS**

Number of lights	2
Wattage of light	40
Type of light	incandescent

#### **DUCTING / RECIRCULATION**

Ducting	yes
Top or rear duct hole	top
Recirculation option	Yes
Recirculation kit	optional accessory



# **DUCTING / RECIRCULATION**

Optional extension flue	Yes
Length of extension flue	1100



## **Terms and Conditions**

#### **IMPORTANT**

This is a guide of product dimensions only. For complete installation instructions, refer to the manual provided with product.

#### PRODUCT INFORMATION

The descriptors and illustrations in this publication apply to the specific products and models described as at the date of issue. Under our policy of continuous productdevelopment, product specifications may change without notice. Prospective purchasers should therefore check with their retailer to ensure this publication correctly describes the products that are being offered for sale. All information supplied is to be used for general reference purposes only and is on the understanding that Electrolux Home Products PtyLtd (Australia) and Electrolux (NZ) Ltd (New Zealand) will not be liable for any loss, liability or damage of whatever kind arising as a result of reliance on such information. Colours of products illustrated are as close as printing limitations allow. Electrolux will at all times comply with its obligations pursuant to law including Trade Practices (Australian Consumer Law) Act and Regulations.

#### WARRANTY

This warranty only applies to Appliances purchased and used in Australia or New Zealand and used in normal domestic applications and is in addition to (and does not exclude, restrict, or modify in any way) any non-excludable statutory warranties in Australia or New Zealand. All warranties are subject to the conditions set out in the warranty card accompanying the product when purchased.

#### **ELECTROLUX HOME PRODUCTS AUSTRALIA**

telephone: 1300 363 640 fax: 1800 350 067

email: customercare@electrolux.com.au

web: www.electrolux.com.au

**ELECTROLUX HOME PRODUCTS NEW ZEALAND** 

telephone: 09 573 2230 fax: 09 573 2221

email: customercare@electrolux.co.nz

web: www.electrolux.co.nz